

*Page TC4-1 Lines 15 through 22*

Section 4C.02 <del>Warrant</del> <u>Criteria</u> 1, Eight-Hour Vehicular Volume.....	4C-3
Section 4C.03 <del>Warrant</del> <u>Criteria</u> 2, Four-Hour Vehicular Volume.....	4C-6
Section 4C.04 <del>Warrant</del> <u>Criteria</u> 3, Peak Hour.....	4C-6
Section 4C.05 <del>Warrant</del> <u>Criteria</u> 4, Pedestrian Volume.....	4C-8
Section 4C.06 <del>Warrant</del> <u>Criteria</u> 5, School Crossing.....	4C-11
Section 4C.07 <del>Warrant</del> <u>Criteria</u> 6, Coordinated Signal System.....	4C-12
Section 4C.08 <del>Warrant</del> <u>Criteria</u> 7, Crash Experience.....	4C-12
Section 4C.09 <del>Warrant</del> <u>Criteria</u> 8, Roadway Network.....	4C-13

*Page TC4-2, Line 7*

Section 4D.21	Traffic <del>Signal</del> Signs, Auxiliary.....	4D-36
---------------	---	-------

*Page TC4-3 Lines 17 through 20*

Figure 4C-1 <del>Warrant</del> <u>Criteria</u> 2 – Four-Hour Vehicular Volume .....	4C-7
Figure 4C-2 <del>Warrant</del> <u>Criteria</u> 2 – Four-Hour Vehicular Volume (70% Factor).....	4C-7
Figure 4C-3 <del>Warrant</del> <u>Criteria</u> 3 – Peak Hour.....	4C-9
Figure 4C-3 <del>Warrant</del> <u>Criteria</u> 3 – Peak Hour (70% Factor).....	4C-9

*Page TC4-3, Line 24*

Figure 4D-2	<u>Typical</u> Horizontal <u>and</u> <u>Longitudinal</u> Location of Signal Faces.....	4D-26
-------------	--	-------

*Page TC4-3, Line 28 & 29*

Figure 4E-2	<u>Recommended</u> <u>Typical</u> Pushbutton Locations for Accessible Pedestrian Signals.....	4E-11
-------------	--	-------

*Page TC4-4, Line 3*

Table 4C-1	<del>Warrant</del> <u>Criteria</u> 1, Eight-Hour Vehicular Volume.....	4C-5
Table 4C-1a	Eight Hour Vehicular Volume (ADT Equivalent).....	4C-5
Table 4C-2	Mathematical Equation Equivalency To Figure 4C-1 .....	4C-6
Table 4C-3	Mathematical Equation Equivalency To Figure 4C-2 .....	4C-6
Table 4C-4	Mathematical Equation Equivalency To Figure 4C-3 .....	4C-8
Table 4C-5	Mathematical Equation Equivalency To Figure 4C-4 .....	4C-8
Table 4C-6	Vehicular Volume Equivalency For Insufficient Gaps in Vehicular Flow.....	4C-12

*Page 4A-6, Line 11*

**62. Signal ~~Warrant~~ Criteria-a threshold condition that, if found to be satisfied as part**

*Page 4B-1 Section 4B.02 Line 25*

has provided a series of signal ~~warrants~~ criteria, described in Chapter 4C, that defines the ~~minimum~~

*Page 4B-2, Section 4B.02, Line 9*

D. Flash or cover the signal heads for a ~~minimum of 90 days~~ period of time, and install the appropriate

*Page 4B-2, Section 4B.02, Line 13*

control signal, the poles and cables may remain in place ~~for 1 year~~ after removal of the

*Page 4B-2, Section 4B.03, Lines 24 & 25*

and control measures are used, and if the signal timing is reviewed and updated, as needed, ~~on a regular basis (every 2 years)~~ to ensure that it satisfies current traffic demands.

*Page 4B-2 Section 4B.03 Line 26*

C. They potentially reduce the frequency and severity of certain types of crashes, especially right-angle

*Page 4B-2, Section 4B.03, Line 28*

D. They are capable of being coordinated to provide for continuous or nearly continuous movement of traffic

*Page 4B-2, Section 4B.03, Line 30*

E. They ~~are~~ can potentially be used to interrupt heavy traffic at intervals to permit other traffic, vehicular or

*Page 4B-3, Section 4B.03, Line 12*

Engineering ~~studies~~ reviews of operating traffic control signals ~~should be made~~ may become necessary, when operational conditions change, to determine whether

*Page 4B-3, Section 4B.04, Line 19*

signal ~~warrants~~ criteria has been satisfied.

*Page 4B-4, Section 4B.04, Line 7*

J. If the ~~warrant~~ criteria is satisfied, installing multiway Stop sign control:

*Page 4B-4, Section 4B.05, Line 22 & 23*

intersection is widened, consideration should be given to the additional green time pedestrians need to cross the widened roadways ~~should be considered to ensure that it will not exceed~~ as compared to the green time saved

*Page 4C-1, Section 4C.01, Line 4*

**An engineering study of traffic conditions, pedestrian ~~characteristics~~ conditions, and**

*Page 4C-1, Section 4C.01, Line 8*

**of the applicable factors contained in the following traffic signal ~~warrants~~ criteria and other**

*Page 4C-1, Section 4C.01, Lines 10 through 17*

**Warrant Criteria 1, Eight-Hour Vehicular Volume.**

**Warrant Criteria 2, Four-Hour Vehicular Volume.**

**Warrant Criteria 3, Peak Hour.**

**Warrant Criteria 4, Pedestrian Volume.**

**Warrant Criteria 5, School Crossing.**

**Warrant Criteria 6, Coordinated Signal System.**

**Warrant Criteria 7, Crash Experience.**

**Warrant Criteria 8, Roadway Network.**

*Page 4C-1, Section 4C.01, Between Lines 17 & 18*

**Criteria 1 and 4 are considered warrants. Criteria 2, 3, 5, 6, 7 and 8 are considered guidelines.**

*Page 4C-1, Section 4C.01, Line 18*

**The satisfaction of a one or more traffic signal ~~warrant or warrants~~ or guidelines shall not in itself require**

*Page 4C-1, Section 4C.01, Lines 27 and 28*

A traffic control signal should not be installed unless an engineering ~~study~~ analysis indicates that installing a traffic control signal will potentially improve the ~~overall~~ safety and/or operation of

*Page 4C-1, Section 4C.01, Line 31*

traffic flow within an existing traffic signal system.

*Page 4C-2, Section 4C.01, Line 4*

count against the above signal ~~warrants~~ criteria.

*Page 4C-2, Section 4C.01, Line 5*

Engineering judgment should also be used in applying various traffic signal ~~warrants~~ criteria

*Page 4C-2, Section 4C.01, Line 19*

major street with minimal conflict and the right turn lane is of sufficient length to accommodate the expected right turning traffic. Under the proceeding conditions, ~~The~~ approach should be evaluated as a one-lane

*Page 4C-2, Section 4C.01, Line 22*

to obtain a traffic count that would represent future conditions, hourly volumes or average daily traffic

*Page 4C-2, Section 4C.01, Line 24*

~~warrants~~ criteria.

*Page 4C-2, Section 4C.01, Line 25*

For signal ~~warrant~~ criteria analysis, a location with a wide median should be considered as

*Page 4C-2, Section 4C.01, Between Lines 27 & 28*

The study may consider the effects of the right turn vehicles and the associated permitted movement on a “Red” signal indication after a stop, under assumed traffic signal operation, from all the approaches. Engineering judgment should be used to determine what, if any, portion of the right turn traffic is subtracted from the approach traffic count when evaluating the vehicular traffic count against the traffic signal criteria.

Satisfaction of a single traffic signal criteria, with a documented engineering study/review, can be justification for the installation of a traffic signal at a specific location.

*Page 4C-2, Section 4C.01, Lines 32 through 37*

- B. Vehicular volumes for each traffic movement from each approach, which may be classified by vehicle type (~~heavy trucks, or passenger cars and light trucks, public transit vehicles,~~ and, in some locations, ~~bicycles school buses~~), during each 15-minute period of the 2 hours in the morning and 2 hours in the afternoon during which total traffic entering the intersection is greatest.
- C. Pedestrian volume counts on each crosswalk during ~~the same periods as the vehicular counts in Paragraph B above and during~~ hours of highest pedestrian volume. Where

*Page 4C-3, Section 4C.01, Line 17*

severity, weather, time of day, date, and day of week for ~~at least 1 year~~ a desirable period of three or more years, if the information is available.

*Page 4C-3, Section 4C.01, Line 19*

the intersection, may be obtained: ~~during the periods specified in Paragraph B above:~~

*Page 4C-3, Section 4C.01, Line 21*

consistent with the Peak Hour ~~Warrant~~ Criteria.

*Page 4C-3, Section 4C.01, Line 24*

- C. The posted or, if not posted, statutory speed limit or the known 85th-percentile speed on controlled approaches

*Page 4C-3, Section 4C.02, Line 29*

**Section 4C.02 ~~Warrant~~ Criteria 1. Eight-Hour Vehicular Volume**

*Page 4C-3, Section 4C.02, Line 31*

The Minimum Vehicular Volume, Condition A or A1, is intended for applications where a large

*Page 4C-3, Section 4C.02, Line 33*

The Interruption of Continuous Traffic, Condition B or B1, is intended for application where the

*Page 4C-4, Section 4C.02, Between Line 14 & 15*

When comparing vehicular volume of both approaches of the major street against the volume of the side street approaches, each side street approach may independently be evaluated against the criteria listed in Condition A and Condition B of Table 4C-1.

Temporary traffic signals may be installed at new intersections, on predicted hourly vehicular volumes, providing the predicted volumes meet the prescribed minimum vehicular volume levels as noted in Condition A or Condition B of TABLE 4C-1.

Temporary traffic signals may be installed at new intersections, on predicted average daily traffic volumes, providing the predicted volumes meet prescribed minimum levels as noted in Condition A1 or Condition B1 of TABLE 4C-1a. The temporary traffic signals may be placed in signal operation until proper traffic data and experience can be obtained.

Temporary traffic signals may become permanent traffic signals only after the completion of a traffic engineering investigation that verifies that permanent traffic signals are justified.

1. The traffic volumes used shall be assigned current volumes.

2. Conditions A1 or B1 lists the minimum Average Daily Traffic volumes which may justify consideration of signalization, and which are considered to be equivalent to the hourly traffic volume stipulations denoted by Condition A and Condition B respectively.
3. Surveillance should be maintained on the temporary traffic signal to assure that the signal operation is not creating any undue problems.
4. An engineering study should be conducted, normally, after six months of operation and before one year of operation as a temporary traffic signal control, to determine if the traffic signal is needed and should become a permanent installation.
5. If the temporary traffic signal is not justified by an engineering study, it may be removed immediately and the appropriate traffic control devices, commensurate to justification revealed by the engineering study, may be installed.
6. If the engineering study indicates that the traffic signal is justified, it shall remain in place and have the status of a permanent traffic signal installation.

Temporary traffic signals installed under this procedure must conform to the design requirements for traffic signals as stipulated in this manual.

*Page 4C-5, Section 4C.02, Line 1*

**Table 4C-1. ~~Warrant~~ Criteria 1, Eight-Hour Vehicular Volume**

*Page 4C-5, Section 4C.02, Line 23*

<sup>b</sup> Used for combination of Conditions A and B after ~~adequate trial~~ adequate trial consideration of other remedial measures.

*Page 4C-5, Section 4C.02, After Line 25*

**TABLE 4C-1a, Eight-Hour Vehicular Volume (ADT Equivalent)**

Condition A1 – Minimum Vehicular Volume (ADT Equivalent)			
<u>Number of lanes on each approach</u>		<u>Equivalent Average Daily Traffic Volumes Approaching From Both Directions On:</u>	
<u>Major Street</u>	<u>Minor Street</u>	<u>Major Street</u>	<u>Minor Street</u>
<u>1</u>	<u>1</u>	<u>8,300</u>	<u>4,600</u>
<u>2 or more</u>	<u>1</u>	<u>10,000</u>	<u>4,600</u>
<u>2 or more</u>	<u>2 or more</u>	<u>10,000</u>	<u>6,000</u>
<u>1</u>	<u>2 or more</u>	<u>8,300</u>	<u>6,000</u>

Condition B1 – Interruption of Continuous Traffic (ADT Equivalent)			
<u>Number of lanes on each approach</u>		<u>Equivalent Average Daily Traffic Volumes Approaching From Both Directions On:</u>	
<u>Major Street</u>	<u>Minor Street</u>	<u>Major Street</u>	<u>Minor Street</u>
<u>1</u>	<u>1</u>	<u>12,500</u>	<u>2,300</u>
<u>2 or more</u>	<u>1</u>	<u>15,000</u>	<u>2,300</u>
<u>2 or more</u>	<u>2 or more</u>	<u>15,000</u>	<u>3,100</u>
<u>1</u>	<u>2 or more</u>	<u>12,500</u>	<u>3,100</u>

*Page 4C-6, Section 4C.02, Lines 2 through 4*

The combination of Conditions A and B should be applied only after ~~an adequate trial~~ adequate trial consideration of other alternatives that could cause less delay and inconvenience to traffic ~~has failed to solve the traffic problems.~~

Page 4C-6, Section 4C.03, Lines 5

**Section 4C.03 ~~Warrant~~ Criteria 2, Four-Hour Vehicular Volume**

Page 4C-6, Section 4C.03, Lines 7

The Four-Hour Vehicular Volume signal ~~warrant~~ criteria conditions are intended to be applied where

Page 4C-6, Section 4C.03, Between Lines 18 & 19

When comparing vehicular volumes depicted in Figure 4C-1, the appropriate equations, as listed in Table 4C-2, may be used.

**Table 4C-2. Mathematical Equation Equivalency to Figure 4C-1**

X = sum of both major street approach volumes		
Y = volume of a) single minor street approach or b) minor street high volume approach		
Number of Lanes		
Minor Street(Y)	Major Street(X)	Equation
2 or more	2 or more	If $X \geq 1295$ , $Y = 115$ or $Y = 879.232228 - 1.011380233X + 0.0003253082X^2$
2 or more	1	If $X \geq 1118$ , $Y = 115$ or $Y = 651.50622395 - 0.7483745392X + 0.000240228X^2$
1	2 or more	If $X \geq 1340$ , $Y = 80$ or $Y = 651.50622395 - 0.7483745392X + 0.000240228X^2$
1	1	If $X \geq 1142$ , $Y = 80$ or $Y = 554.1310944 - 0.7134267844X + 0.0002312157X^2$

Page 4C-6, Section 4C.03, Between Lines 21 & 22

When comparing vehicular volumes depicted in Figure 4C-2, the appropriate equations, as listed in Table 4C-3, may be used.

**Table 4C-3. Mathematical Equation Equivalency to Figure 4C-2**

X = sum of both major street approach volumes		
Y = volume of a) single minor street approach or b) minor street high volume approach		
Number of Lanes		
Minor Street(Y)	Major Street(X)	Equation
2 or more	2 or more	If $X \geq 890$ , $Y = 80$ or $Y = 613.77772474 - 0.9893678281X + 0.0004377428X^2$
2 or more	1	If $X \geq 797$ , $Y = 80$ or $Y = 460.53837044 - 0.7635806818X + 0.0003591016X^2$
1	2 or more	If $X \geq 940$ , $Y = 60$ or $Y = 460.53837044 - 0.7635806818X + 0.0003591016X^2$
1	1	If $X \geq 782$ , $Y = 60$ or $Y = 377.22710663 - 0.6793503652X + 0.0003501046X^2$

When comparing vehicular volume of both approaches of the major street against the volume of the side street approaches, each side street approach may independently be evaluated against the criteria listed in Figure 4C-1, 4C-2, Table 4C-2 or Table 4C-3, as appropriate.

Page 4C-6, Section 4C.04, Line 22

**Section 4C.04 ~~Warrant~~ Criteria 3, Peak Hour**

Page 4C-6, Section 4C.04, Line 24

The Peak Hour signal ~~warrant~~ criteria is intended for use at a location where traffic conditions are

Page 4C-6, Section 4C.04, Line 28

This signal ~~warrant~~ criteria shall be applied only in unusual cases, Such cases include,

Page 4C-7, Section 4C.03, Line 1

**Figure 4C-1. ~~Warrant~~ Criteria 2 – Four-Hour Vehicular Volume**

Page 4C-7, Section 4C.03, Line 30

**Figure 4C-2. ~~Warrant~~ Criteria 2 – Four-Hour Vehicular Volume (70% Factor)**

Page 4C-8, Section 4C.04, Line 5

1. **The total stopped time delay experienced, or estimated by the method described in the Highway Capacity Manual for unsignalized intersections, by the traffic on one minor-**

Page 4C-8, Section 4C.04, Between Lines 21 & 22

When comparing vehicular volumes depicted in Figure 4C-3, the appropriate equations, as listed in Table 4C-4 may be used.

**Table 4C-4. Mathematical Equation Equivalency to Figure 4C-3**

<u>X = sum of both major street approach volumes</u>		
<u>Y = volume of a) single minor street approach or b) minor street high volume approach</u>		
<u>Number of Lanes</u>		
<u>Minor Street(Y)</u>	<u>Major Street(X)</u>	<u>Equation</u>
<u>2 or more</u>	<u>2 or more</u>	$\text{If } X \geq 1672, Y = 150 \text{ or } Y = 1060.5405451 - 0.889969286X + 0.0002059999X^2$
<u>2 or more</u>	<u>1</u>	$\text{If } X \geq 1461, Y = 150 \text{ or } Y = 837.59424427 - 0.7219511908X + 0.0001720248X^2$
<u>1</u>	<u>2 or more</u>	$\text{If } X \geq 1759, Y = 100 \text{ or } Y = 837.59424427 - 0.7219511908X + 0.0001720248X^2$
<u>1</u>	<u>1</u>	$\text{If } X \geq 1516, Y = 100 \text{ or } Y = 745.652000052 - 0.7548866636X + 0.00021703X^2$

Page 4C-8, Section 4C.04, Between Lines 25 & 26

When comparing vehicular volumes depicted in Figure 4C-4, the appropriate equations, as listed in Table 4C-5 may be used.

**Table 4C-5. Mathematical Equation Equivalency to Figure 4C-4**

<u>X = sum of both major street approach volumes</u>		
<u>Y = volume of a) single minor street approach or b) minor street high volume approach</u>		
<u>Number of Lanes</u>		
<u>Minor Street(Y)</u>	<u>Major Street(X)</u>	<u>Equation</u>
<u>2 or more</u>	<u>2 or more</u>	$\text{If } X \geq 1183, Y = 100 \text{ or } Y = 771.842673 - 0.9817221615X + 0.0003498922X^2$
<u>2 or more</u>	<u>1</u>	$\text{If } X \geq 1040, Y = 100 \text{ or } Y = 593.38729059 - 0.7471500045X + 0.000262383X^2$
<u>1</u>	<u>2 or more</u>	$\text{If } X \geq 1196, Y = 75 \text{ or } Y = 593.38729059 - 0.7471500045X + 0.000262383X^2$
<u>1</u>	<u>1</u>	$\text{If } X \geq 1054, Y = 75 \text{ or } Y = 520.01155026 - 0.7647561999X + 0.0003250549X^2$

When comparing vehicular volume of both approaches of the major street against the volume of the side street approaches, each side street approach may independently be evaluated against the criteria listed in Figure 4C-3, 4C-4, Table 4C-4 or Table 4C-5, as appropriate.

Page 4C-8, Section 4C.05, Line 26

**Section 4C.05 ~~Warrant~~ Criteria 4, Pedestrian Volume**

*Page 4C-8, Section 4C.05, Line 28*

The Pedestrian Volume signal ~~warrant~~ criteria is intended for applications where the traffic volume on

*Page 4C-9, Section 4C.04, Line 1*

**Figure 4C-3. ~~Warrant~~ Criteria 3 – Peak Hour**

*Page 4C-9, Section 4C.04, Line 31*

**Figure 4C-2. ~~Warrant~~ Criteria 3 – Peak Hour (70% Factor)**

*Page 4C-10, Section 4C.05, Line 13*

**The Pedestrian Volume signal ~~warrant~~ criteria shall not be applied at locations where**

*Page 4C-10, Section 4C.05, Line 17*

**If a traffic signal control signal is justified by both this signal ~~warrant~~ criteria and a traffic**

*Page 4C-10, Section 4C.05, Line 21*

If a traffic signal control signal is justified by both this signal ~~warrant~~ criteria and a traffic

*Page 4C-10, Section 4C.05, Lines 25 through 27*

B. At an intersection, the traffic control signal ~~should be traffic actuated and should include pedestrian detectors if semi-actuated. As a minimum, it should have semi-actuated operation, but if Full-actuated operation with detectors on all approaches might also~~

*Page 4C-11, Section 4C.06, Line 7*

**Section 4C.06 ~~Warrant~~ Criteria 5, School Crossing**

*Page 4C-11, Section 4C.06, Line 9*

The School Crossing signal ~~warrant~~ criteria is intended for application where the fact that school

*Page 4C-11, Section 4C.06, Line 23*

**The School Crossing signal ~~warrant~~ criteria shall not be applied at locations where the**

*Page 4C-11, Section 4C.06, Between Lines 27 & 28*

As an alternate to obtaining the actual number of available gaps, of adequate length, to permit for the safe crossing of the street by school children, actual vehicular volumes traversing the school cross-walk can be compared to the conditions denoted in Table 4C-6 for the purpose of determining the potential need for a traffic signal.



**Table 4C-6. Vehicular Volume Equivalency For Insufficient Gaps In Vehicular Flow**

Average Number of Children Per Minute	Width of Street Vehicular Volume (v.p.h.)			
	30'	40'	50'	60'
1 - 5	645	610	570	530
6 - 10	620	580	545	505
11 - 15	590	555	515	480
16 - 20	565	530	490	450
21 - 25	540	500	465	425
26 - 30	510	475	435	400
31 - 35	485	450	410	370

Page 4C-11, Section 4C.06, Line 28

If a traffic control signal is justified by both this signal ~~warrant~~ criteria and an engineering

Page 4C-12, Section 4C.06, Lines 1 through 3

B. At an intersection, the traffic control signal ~~should be traffic actuated and~~ should include pedestrian detectors if semi-actuated. ~~As a minimum, it should have semi-actuated operation, but if~~ Full-actuated operation with detectors on all approaches might also

Page 4C-12, Section 4C.07 Line 9

**Section 4C.07 ~~Warrant~~ Criteria 6, Coordinated Signal Systems**

Page 4C-12 Section 4C.07, Line 16

**finds that one of the following ~~criteria~~ conditions is met:**

Page 4C-12, Section 4C.07, Line 24

The Coordinated Signal System signal ~~warrant~~ criteria should not be applied where the

Page 4C-12 Section 4C.07 Between Lines 25 & 26

The Coordinated Signal System signal criteria should not be applied where the resultant traffic signal would be the first signal in the signal system.

Page 4C-12, Section 4C.08, Line 26

**Section 4C.08 ~~Warrant~~ Criteria 7, Crash Experience**

Page 4C-12, Section 4C.08, Line 28

The Crash Experience signal ~~warrant~~ criteria conditions are intended for application where the

Page 4C-13, Section 4C.08, Line 3

**finds that all of the following ~~criteria~~ conditions are met:**

*Page 4C-13, Section 4C.09, Line 19*

**Section 4C.09 ~~Warrant~~ Criteria 8, Roadway Network**

*Page 4C-13, Section 4C.09, Line 26*

**of the following ~~criteria~~ conditions:**

*Page 4C-14, Section 4C.09, Line 1*

**A major route as used in this signal ~~warrant~~ criteria shall have one or more of the following**

*Page 4C-14, Section 4C.09, Line 5*

**B. It includes rural or suburban highways which are outside adjacent to, entering, or traversing a**

*Page 4D-1, Section 4D.01, Line 26*

**control signal, the signal faces shall be covered, ~~turned~~, or taken down to clearly**

*Page 4D-2, Section 4D.01, Line 3*

**should be ~~re-evaluated regularly and updated if needed~~ reviewed and updated, as needed to ensure that it satisfies current traffic demand.**

*Page 4D-5, Section 4D.04, Lines 3 & 4*

**Except when a sign is in place prohibiting a turn on red ~~or a RED ARROW signal indication is displayed~~, vehicular traffic facing a**

*Page 4D-5, Section 4D.04, Lines 10 through 18*

**2. ~~Vehicular traffic facing a steady RED ARROW signal indication shall not enter the intersection to make the movement indicated by the arrow (except as described in the Option below) and, unless entering the intersection to make another movement permitted by another signal indication, shall stop at a clearly marked stop line; but if there is no stop line, before entering the crosswalk on the near side of the intersection, or if there is no crosswalk, then before entering the intersection, and shall remain stopped until a signal indication permitting the movement indicated by such RED ARROW is shown.~~**

*Page 4D-5, Section 4D.04, Line 20*

**a steady CIRCULAR RED ~~or RED ARROW~~ signal indication alone shall**

*Page 4D-5, Section 4D.04, Lines 34 through 36*

**3. ~~Flashing RED ARROW and~~ A flashing YELLOW ARROW signal indications ~~have~~ has the same meaning as the corresponding flashing circular signal indication, except ~~they apply~~ it applies only to the vehicular traffic**

*Page 4D-6, Section 4D.04, Lines 1 through 3*

~~Option:~~

~~Where turns are allowed on red and the signal indication is an arrow, a sign may be used to indicate that turns are allowed on red after stopping.~~

*Page 4D-7, Section 4D.05, Lines 4 through 8*

~~D. A steady RED ARROW signal indication shall be displayed when it is intended to prohibit traffic, except pedestrians directed by a pedestrian signal head, from entering the intersection or other controlled area to make the indicated turn. Turning on a steady RED ARROW signal indication shall not be permitted.~~

*Page 4D-7, Section 4D.05, Lines 17 & 18*

2. Shall not be displayed in conjunction with the change from a CIRCULAR RED ARROW signal indication to a GREEN ARROW signal indication.

*Page 4D-7 Section 4D.05 Lines 23 & 24*

4. Shall be terminated by a ~~RED ARROW~~ signal indication for the same direction or a CIRCULAR RED signal indication except:

*Page 4D-7, Section 4D.05, Line 27*

**YELLOW ARROW** signal indication. (see Section 4D.13)

*Page 4D-8, Section 4D.05, Line 14*

Steady ~~RED ARROW~~, YELLOW ARROW, and GREEN ARROW signal indications, if not

*Page 4D-9, Section 4D.06, Lines 12 through 18*

~~1. Left turn RED ARROW, YELLOW ARROW, and GREEN ARROW signal indications only. At least one left turn signal face shall be provided in addition to the two approach signal faces required in Section 4D.15 for the through movement. Only one of the three colors shall be illuminated at any given time. A signal instruction sign shall not be required with this set of signal indications. If used, it shall be a LEFT ON GREEN ARROW ONLY sign (R10-5); or~~

*Page 4D-9, Section 4D.06, Lines 25 through 27*

it cannot be seen by drivers in the through lane(s), either a LEFT TURN SIGNAL sign (R10-10) or a LEFT ON ARROW ONLY sign (R10-Y5) ~~or a visibility limited CIRCULAR RED signal indication~~ shall be used.

*Page 4D-12, Section 4D.07, Lines 15 through 17*

through traffic, ~~except that if the right turn is held to provide an exclusive pedestrian movement, a separate right turn RED ARROW signal indication shall be provided.~~

*Page 4D-12, Section 4D.07, Lines 20 through 26*

**~~1. Right turn RED ARROW, YELLOW ARROW, and GREEN ARROW signal indications only.~~**  
**~~At least one right turn signal face shall be provided in addition to the two approach signal faces required in Section 4D.15 for the through movement. Only one of the three colors shall be illuminated at any given time. A signal instruction sign shall not be required with this set of signal indications. If used, it shall be a RIGHT ON GREEN ARROW ONLY sign (R10-5a); or~~**

*Page 4D-14, Section 4D.08, Line 16*

**~~A straight through RED ARROW signal indication or a straight-through~~**

*Page 4D-15, Section 4D.09, Lines 4 through 12*

**~~Guidance:~~**

**~~— No movement that creates an unexpected crossing of pathways of moving vehicles or pedestrians should be allowed during any green or yellow interval, except when all three of the following conditions are met:~~**

- ~~A. The movement involves only slight conflict, and~~**
- ~~B. Serious traffic delays are substantially reduced by permitting the conflicting movements, and~~**
- ~~C. Drivers and pedestrians subjected to the unexpected conflict are effectively warned thereof by a sign.~~**

*Page 4D-15, Section 4D.10, Line 16*

**~~GREEN or GREEN ARROW signal indication, except as noted in section 4H.02.~~**

*Page 4D-16, Section 4D.11, Lines 22 and 23*

**~~left turn movements shall be permitted to flash a CIRCULAR RED or RED ARROW signal indication when the through signal indications are flashed~~**

*Page 4D-16, Section 4D.11, Lines 27 and 28*

**~~C. The appropriate RED ARROW or YELLOW ARROW signal indication shall be flashed when a signal face consists entirely of arrow lenses.~~**

*Page 4D-23, Section 4D.15, Line 17*

**~~D. Locations where there is significant percentage of elderly drivers~~ are of special concern.**

*Page 4D-23, Section 4D.15, Line 22*

**~~the approach, even if the major movement is a turning movement.~~**

*Page 4D-26, Section 4D.15, Line 1*

**Figure 4D-2. Typical Horizontal and Longitudinal Location of Signal Faces**

*Page 4D-27, Section 4D.15, Lines 15 and 16*

**~~mode left-turn movement, or if a left-turn movement represents the major movement from an approach,~~**  
**~~two left-turn signal faces should be provided.~~**

*Page 4D-27, Section 4D.15, Lines 18 and 19*

movement, ~~or if a right turn movement represents the major movement from an approach,~~ two right-turn signal faces should be provided.

*Page 4D-27, Section 4D.15, Line 21*

If a signal face controls a specific movement from a lane or lanes of an approach, its position should make

*Page 4D-28, Section 4D.16, Lines 9 and 10*

**Each signal face at a signalized location shall have ~~either three, four, or~~ one to five signal sections. For usage of a two section signal face, see section 4H.02.**

*Page 4D-28, Section 4D.16, Line 11*

**A single-section signal face shall only be permitted at a traffic control signal if it**

*Page 4D-29, Section 4D.16, Lines 16 and 17*

**~~Left turn RED ARROW~~**

**~~Right turn RED ARROW~~**

*Page 4D-29, Section 4D.16, Lines 27 and 28*


**~~Left turn RED ARROW~~**

**~~Right turn RED ARROW~~**

December 2000

Page 4D-31

**Figure 4D-3. Typical Arrangements of Signal Lenses in Signal Faces**



*Page 4D-35, Section 4D.20, Line 16*

**transported and used at different locations. Portable traffic control signals shall not be permitted upon the roadway system.**

*Page 4D-36, Section 4D.20, Line 2*

**operate the signal, or the signal heads shall be covered, ~~turned~~, or taken**

*Page 4D-36, Section 4D.21, Lines 19 and 20*

**The minimum clearance of the total assembly of traffic signal signs (~~see Section 2B.40~~) shall conform to the provisions of Section 4D.17.**

*Page 4D-36, Section 4D.21, Line 21*

**If used, illuminated traffic ~~signal~~ signs shall be designed and mounted in such a**

*Page 4D-36, Section 4D.21, Line 26*

When a traffic ~~signal~~ sign at a highway traffic signal is applicable to a particular

*Page 4E-2, Section 4E.03, Line 6*

**either ~~Warrant~~ Criteria 4, Pedestrian Volume or ~~Warrant~~ Criteria 5, School Crossing (see**

*Page 4-2, Section 4E.03, Lines 12 & 13*

**~~D. When multiphase signal indications (as with split phasing) would tend to confuse pedestrians guided only by vehicular signal indications.~~**

*Page 4E-3, Section 4E.04, Line 27*

Pedestrian signal indications should be ~~conspicuous~~ visible and recognizable to pedestrians

*Page 4E-6, Section 4E.06, Line 8*

**Under ~~stop-and-go~~ steady mode operation, accessible pedestrian signals shall not be limited**

*Page 4E-11, Section 4E.08, Line 1*

**Figure 4E-2. Recommended Typical Pushbutton Locations**